FUNCTION RELEASED OR CONTROLLED							BY			REMARKS
	The second state of the se	LEVER	LEVER		TION	TRACK CLC			and the second se	
			LOCKED	NORMAL	REVERSE	CLEAR	0CC'D	L.C.	T. O. L.	
8 (R) L						117. 28T. (13T WIZR)				ELN
11 (R) L					- Andrews	11T. 13T. 40T. (23+ W242)				ELN
13 (R) L						117 131				ELN
21 (N) L		1	8.13.28.R 55N	27A	28	IIT.137.287.56T.				
23 (R) L						23т.				ELN
28 (R) L						28T. (11TW5R) (13TW12R) (23T.40TW27R)				ELN
27 (N) L	<u>n</u> 1					287. 407.	an den sterling)			
33 ATC	33D	33R	-							
41 (N) L	42 ON		42.62N.			41T. 65T.				
42 (N) L		•				•		UP MAIN		ONE PULL AFTER AIT OCCUPIED.
44 (N) L		45N	23R			237	•			
50 (N) L						. :		TOKEN OUT		
52 (N) L		50N	21N.28R. 44N.		27n. 28.					
54 (N) L								DOWN MAIN		ONE PULL AFTER 55T OCCUPIED
55 (N) L	54 or		54			557				
56 (N) L			28R.55N	27A	28	287. 567.				
57 (N) L			52.56N.			57 т.				
58 ATC	580	58R								
,			DATED ISSUED		PATNEY & CHIRTON				C 270 /5/	
			CORRECT TO G		ELECTRICAL	S 379 /5/I				

RELEASED OR CONTROLLED BY								REMARKS	
SIGNAL							service by the state of the local service of the se	The second se	
			NORMAL	REVERSE	CLEAR	OCCD	L.C.	1. O. L.	
420N		41.42N. 65R			41T. 65T.				
					657				ELN
					40T				ELN
34.40. 42 off	33R								
54.57 OFF	58R								
340N 33 AT H	34				* *	•			
57 ON 58 AT H		57N							
								112 / A	
-	-								
				то G					S 379 / 5/2
	SIGNAL 420N 34.40. 420FF 54.570FF 340N	SIGNAL LEVER 42 on - 34.40. - 34.40. 33R 54.57 off 58R 34 on 34 33 nt H 34 57 on 57 on	SIGNAL LEVER LEVER LEVER 42 on 41.42 n. 42 on 41.42 n. 34.40. 33 R 34.40. 33 R 54.57 off 58 R 34 on 34 33 nt H 57 on	SIGNAL LEVER LEVER DETEC 42 oron 41.42 n. 41.42 n. 34.40: 33 R - - 54.57 off 58 R - - 34 onv 34 - - 35 NT H - - - 57 onv 58 RT H - - 58 RT H - - - 58 RT H - - -	SIGNALLEVERLEVER LOCKEDDETECTION NORMAL42 orv41.42 rv. 65 r41.42 rv. 65 r134.40.33 r1134.40.33 r1154.57 orr58 r1134 orv341133 rr H57 rv57 rv57 rv	SIGNAL LEVER LEVER DETECTION TRACK CIAC LOCKED NORMAL REVERSE CLEAR 42 or 41.42 N 652 440. 34.40. 324.40. 33 R 42 OFF 582 54.57 OFF 582 54.57 OFF 582 54.57 OFF 582 54.57 OFF 582 557 N 33 mm 4 557 N 56 mm 4 557 N 56 mm 4 557 N 58 mm 4 557 N 58 mm 4 557 N 58 mm 4 557 N 58 mm 4 557 N 59 N 59 N 50 N 50 N 50 N 50 N 50 N 50 N 50 N 50	SIGNAL LEVER LEVER LOCKED NORMAL REVERSE CLEAR OCC'D 42000 41.4200 41.4200 41.4200 41.4200 40 40T 40T 40T 40T 40T 40T 40T 40T	SIGNAL LEVER LEVER DETECTION TRACK C.I.CUITS BLOCC 42oro 41.42ro, dosc 41.42ro, dosc 417.65r. 417.65r. 417.65r. 34.40, 42 orpr 33R 401 401 401 401 34.40, 42 orpr 58R. 1 1 1 1 34.40, 42 orpr 58R. 1 1 1 1 34.40, 42 orpr 58R. 1 1 1 1 57.5ref 58R. 1 1 1 1 34 orpr 34 1 1 1 1 57.5ref 58R. 1 1 1 1 57.7 orv 58 mr th 57 rov 57 rov 57 rov 1 58.7 mr th 57 rov 57 rov 57 rov 1 1	SIGNAL LEVER LEVER LOCKED DETECTION TRACK C.I.CUITS BLOCK 42ono 41.42n, 65n 41.42n, 65n 41.65n 1 1 33.40, 42 orp 33R, 54.57 orv 582 1 40T 1 1 34.40, 42 orp 33R, 54.57 orv 582 1 1 1 1 34.40, 42 orp 34 1 1 1 1 1 34.40, 57 orv 582 1 1 1 1 1 34.7 57 orv 58 1 1 1 1