


SER-IAL	DRGS DATE	PLAN No.	DETAILS	OCC'N
			CATCH POINT 30B & DISC 23 PROVIDED	
			DOWN MAIN TO WEYMOUTH DISTANT RECOVERED	
			TC PROVIDED IN REAR OF DOWN HOMES	*
			UP WEYMOUTH OUTER HOME PROVIDED & NUMBERED 52. EXISTING HOME RENUMBERED 51. UP REFUGE SIDING STARTING RENUMBERED 45. TCS PROVIDED - AB, CD, (EF. GH ?) C.O. SIGNAL 47 ADDED?	7.1910 by 1919
			UP & DOWN DETONATORS PROVIDED	
			DISC 37 RECOVERED, POINTS 38 MADE W.P / 40 (IF EVER CONNECTED)	
			UP MAIN STARTING & C.O. MOVED TO DOWN SIDE	1922 - 24
			TRAP POINT 20 RECOVERED. DISC 21 REPOSITIONED ADJACENT TO UP MAIN.	
			ADDITIONAL HOME FROM SOMERTON PROVIDED. DISTANT REPOSITIONED & MOTOR OP. TC PROVIDED (FF) AND EE ADJUSTED. FRAME EXTENDED TO 56 LEVERS.	7.1910



* R160 AUTH TRAFFIC CTTEE
FEB 1910 = TWO TCS?

CASTLE CARY

RECORD OF AMENDMENTS

S 407/1/1

SER-IAL	DRGS DATE	PLAN No.	DETAILS	OCC'N
	1928		MOVEABLE ELBOWS PROVIDED. LEVERS 37 & 38 INTO USE	
			UP MAIN ADV'D STARTING REPOSITIONED & TC IN REAR EXTENDED TO 680x	by 1931
			DOWN MAIN TO WEYMOUTH HOME (No.8) RECOVERED. LOCKING ALTERATION. TC PROVIDED IN REAR OF DOWN INNER HOMES	24.7.1932
12.1934	534/ 425		DOWN WEYMOUTH & DOWN SOMERTON STARTINGS REPOSITIONED. TCS PROVIDED IN REAR & SHUNT ARMS NOT REPRODUCED. 10 BANNER REPEATER PROVIDED.	c. 1936

CASTLE CARY

RECORD OF AMENDMENTS

S 407/1/2

SER-IAL	DRGS DATE	PLAN No.	DETAILS	OCC'N
51975			DN MAIN INNER HOMES RENEWED. UP MAIN INNER HOME & C.O. 1/40 UP MAIN STARTING	3.1.43
			UP & DOWN GOODS LOOPS ADDED	28.3.43
			D.A. ADDED BELOW UP MAIN STARTING	29.4.45
			DISC 51 REPOSITIONED ON DOWN SIDE	8.52
A	9.52		3-SHOT DETONATORS AT UP MAIN & BRANCH HOMES RECOVERED	
			CLOSURE OF WYKE S.B.	4.12.55
B	1.57	SP 56/395	42T & 58T PROVIDED 1/40 LOCKBARS	
C			UP WEYMOUTH DISTANT RENEWED AS CLIGHT. UP WEYMOUTH INNER HOME RENEWED. UP REFUGE SIDING STARTING RENEWED AS DISC	1.7.57. 28.7.57.
D		SP 57/89	DISC 28 ROUTED 2/WAYS & FITTED WITH RED LIGHT.	4.1.58.

CASTLE CARY

RECORD OF AMENDMENTS

S 407 /1/1

SER-IAL	DRGS DATE	PLAN No.	DETAILS	OCC'N
			28 LOCK (31 W 38.592) ADDED FOLLOWING 'D'	
E	8.58		NP DETECTION & ARM PROVING PROVIDED ON POINTS 15	
F			UP TAUNTON DISTANT RENEWED AS 3-ASPECT CLIGHT COMBINED WITH ALFORD STARTING	6.12.59
H			DOWN MAIN DISTANT RENEWED AS 2-ASPECT CLIGHT	22.1.61
I			CLOSURE OF ALFORD S.B. UP TAUNTON DISTANT MADE 2-ASPECT	8.4.62.
J			UP REFUGE SIDING, DN MAIN TO GOODS FACING & 42T RECOVERED.	15.12.63
L			UP MAIN STARTINGS RENEWED - C.O. ARM NOT REPRODUCED	11.3.66
			ARMS OF DOWN MAIN INNER HOMES REPOSITIONED 5FT TO THE LEFT	9.4.67.
			POINTS 21, 68, 69 AND ASSOCIATED SIGNALLING RECOVERED.	18.2.68
		SP 67/33	SINGLING OF WEYMOUTH LINE. DOWN GOODS LOOP MADE PASS'R LOOP	12.5.68.
			UP GOODS LOOP MADE PASS'R LOOP	1.6.69
			UP WEYMOUTH HOME & DISTANT RENEWED 12FT. NEARER LINE	2.11.69

CASTLE CARY

RECORD OF AMENDMENTS

S 407 /1/2