

No.			
1	2.3.4.		
2	19	16.17.	
3	19	16.17.23.	
4		17. (15w 23R)	16.19.23.
5	19.21.	16.17.41.	
6	19.24.	16.17.	
7	19.21.41.	16.17.	
8	x		
9	x		
10	x		
11	x		
12	DETONATOR		
13	x		
14	22	24.32.	
15	16.19. (21 or 24 w 23R)	17.49. (4w 23R)	(41w 21R)
16		2.3.5.6.7.26.31.46.52.	
17		2.3.4.5.6.7.15.	16.19.21.23.24. (22w 23R)(41w 21R)
18	17.24.		
19			23
20		21.32.35.41. (22w 37N) (23.28w 37R)	34.37.
21	23	20.22.32.34.37.43.	
22		21.34.43. (20w 37N)	
23		3.28.33.35.44. (20w 37R) (51w 31N)	
24	22.23.	14.32.	
25	26	27.49.	
26		16.31.52.	
27	26.	25	
28	(42w 37.41R)	23.33.34.44.51. (20w 37R)	37.42.
29	31	37.49.50.51.	
30	38 (42w 41R)	39.45.49.	42
31	23	16.26.34.52.	
32		14.20.21.24.34.43. (37w 22N)	22.41.
33		23.28.34.37.	
34		21.22.28.31.33.37.41.32.51.	
35	34	20.23.	
36	20.34.		
37		21.29.33.34.43.50.51. (32w 22N)	

HACKNEY

S 850/3/1

No.			
38	31.37.		
39	38	30.41.	
40	21	41	
41		5.20.34.39.40.	
42	37.41		
43	41	21.22.32.37.	
44	42	23.28.	
45	38.42.	30.	
46	17.21.41.	16	
47	x		
48	DETONATOR		
49		15.25.29.30.	16.26.31.38. (37.42 w 31R)(41 w 38R)
50	31	29.37.	
51	(31 w 23R)	28.29.34.37. (23 w 31 w)	31
52		16.26.31.	
53	49.52.		
54	x		
55	x		

PRINT ISSUED 3.6.1964 : Amendment D (No.51 made spare)
D 2 x 6.7 added
15 x (41 w 21R) 11/12 (8 w 21R)

PRINT ISSUED FOR OCC'N ON 10.10.1965 (No.1 Spur recovered)
F Nos. 28.33.37.38.39.44 made spare

V.T.
H.T. 3 BAR (WITH TIER OF V.T. ADDED) 1X11 + 1X5
DRAWN : 20.6.1932 "Carried on 1/4" plate"
ISSUED : 17.8.1962 (Amendment B)

Locks (N) 20-R : 3.4.5.6.7.49.50.
- (N) with LCC : 2.52.
- (R) with RD : 19

Contacts 2 Spring : 2.
- 4 - : 1.53.

XW No. 291

HACKNEY

S 850/3/2