

PWLLYRHEBOG

NO	RELEASED BY	LOCKS IN NORMAL POSITION	LOCKS IN EITHER POSITION	RELEASES
1	2.3.4.			
2		6.15.25.38.		1
3		16.25.38	6.15.	1
4		31.39	(21.24w25r)25.37.38	1
5	X			
6		2.10.33.44(24.25w21n)45		7.8.
7	6(14w15r)	8.38.39.43		
8	6	7.14.	15.	(16w6r)
9	10.11.12.			
10		6		9
11		21.24.25.37	6	9
12		29.36.	21.24.25.37	9
13	X			
14	15	8.16. (43w6r)	6	(7w15r)
15		2.25.38		14.16.
16	15(8w6r)	3.14		
17	21.24	25.29		
18	21.25	24.31		
19	X			
20	X			
21		11.22.23.33.37.45.47.		17.18 (31)
22	24	21.25.29.44		
23	24.25	21.31.44		
24		11.18.33.37 (6w21n)46.47		17.22.23.29
25		2.3.11.15.17.22.29.33		18.23.31
		38.45.47 (6w21n)		
26	X			
27		33.46.45.47		

PWLLYRHEBOG

NO	RELEASED BY	LOCKS IN NORMAL POSITION	LOCKS IN EITHER POSITION	RELEASES
28	X			
29	24	12.17.22.25 (44w21r)	21	
30	X			
31	25 (21 or 24)	4.18.23 (44w21r)	21.24	
32	33	40.44		
33		6.21.24.25.27.46. 45.47.		32.40
34	37	36		
35	38	37.39		
36	37	12.34.7		
37	38	11.21.24.35.39		34.36.
38		2.3.15.25		35.37.39
39	38	4.35.37.7		
40	33	32		
41		47		46
42	X			
43		7 (14w6r)	6	
44		6.22.23.32 (29.31w21r)	21.24.25.27.33	48
45		6.21.24.25.27.33	41	48
46	41	27.33		
47		41.21.24.25.27.33		48
48	44.45.47.			
GWR SIGNAL ENGINEER'S OFFICE, READING 22.5.30				