

No	RELEASED BY	LOCKS	NORMAL	LOCKS	BOTH WAYS	RELEASES
1	2.3.4.					
2		13.19.25.28.				1
3		14.16.28.26	(9.12 w 15R)	10.13.15.19.25		1
4		29		28		1
5	x					
6	x					
7	x					
8	9					
9	10	14.16.18.	(3 w 15R)	15.17.		8
10	11.13.	12.				9
11						10.
12	13	10.14.16.18.	(3 w 15R)	15.17.		
13		2.19.22.25.28.34.				10.12.14.15.
14	13	3.9.12.15.		10		
15	13	14.				16.17.
16	15	9.12.17.		10		
17	15	16				18.
18	17	9.12.		10		
19		2.13.22.25.29.34.				
20	x					
21	22	23				
22		13.19.25.34.				21.23.
23	22	21				
24	25	26				
25		2.13.19.22.28.34.				24.26.
26	25	3.24.				
X W	ORIGINAL DRAWN: 31.12.1907 ISSUED: 16.7.1932		HIRWAUN WEST LOCKING TABLE			S /3/1
	REG No. 776					

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
27	28	29		
28		2.3.13.25.		27.29.
29	28	4.19.27.		
30	x			
31	x			
32	x			
33	x			
34		13.19.22.25.		35.
35	34.			
	H.T. 3 BAR 5'4"	(1 x 11)		
	OLD No. 171			
	LOCKING REMOVED	PREVIOUSLY		
2		20		
4		5		
5		4.29.		
13		20.		
20		2.13.29.22.25.34.		
22		20		
25		20		
29		5.20.		
34		20.		
3			20	
X W	ORIGINAL DRAWN: ISSUED:		HIRWAUN WEST LOCKING TABLE	
	REG No.			
			S	13/2

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
1		4.5.15.27.31.33.36.38.40.41.44.45. 48.58. (18w 21n)		
2	x			
3	4.5.6.7.			
4	(5N MSL)	1.17.19.33.36.44.45. (48w 47n)		3
5	(6N MSL)	1.20.33.36.44.45.47.48.	17.19.	3
6		36.45.47.48. (26.31w 32r) (34w 30r. 32n)	30.32.33.34.	3
7		48	47	3
8-12	x			
13	DETONATOR			
14		18.19.23.24.28.42.56.57.58. (34w 21r)(36w 30n. 33r) (37w 30n)(45w 44r)		
15	17	1.20.36.45. (48w 47n)		
16		17		
17		4.16.19.33.44.		15. (20)
18		14.23.24.30.37.42.55.56.57.58. (1w 21n)(20.36.45w 19r)(34w 21r) (36w 33r)(45.48w 33r OR 42r) (48w 19r. 47n)	19.21.32.33.	
19		4.14.17.21.31.33.40.41.44.56.57. 58		(20)
20	(17 OR 19)	5.15. (18w 19r)	1	
21		19.28.31.33.40.41.44.56.57.58.		23.24
22			21	23.24
X W ORIGINAL DRAWN: ISSUED: REG No. 776		HIRWAUN		
		LOCKING TABLE		S /3/1

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
23	21.22.	14.18.24.27.55.		
24	21.22.	14.18.23.27.		
25	28 (26 OR 27)			
26	30	34.45.48. (6W 32R)	28.32.	(25)
27	29	1.23.24.34.	21.28.	(25)
28		14.21.		25
29		30.		27.35
30	33.	18.29.31. (36.37 W 34N)		
31		1.19.21.30.37.42.56.57.58.	32.33.41.	
		(6W 32R)(36W 33R)(45.48 W 33R OR 44R)		
32	33	36.38.45.48.		37.
33		1.4.5.17.19.21.40.41.44.47.58.		30.32.
34	(22OR28)(29OR30)	26.27. (6W 30R.32N)(14.18 W 21R)	28 (32W 30R)	35.
35	29.34.		1	
36		1.4.5.6.15.32.44.47. (14W 30N 33R)	17.19.33.	
		(18W 19R)(18.31W 33R)(30W 34N)		
		(56.57 W 30R)		
37	32.	18.31. (14W 30N)(30W 34N)(56.57W 30R)		
38		1.32.46.	47.	
39	x			
40		1.19.21.33.42.56.57.58. (45.48 W 44R)	41.44.	
41		1.19.21.33.44.58.		42
42	41	14.18.31.40.		
43	44.	45.48.56.57.		
44		1.4.5.17.19.21.33.36.41.47.58		43
X	ORIGINAL DRAWN:	HIRWAUN		
	ISSUED:			
W	REG No.	LOCKING TABLE		S 13/2

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
45		1.4.5.6.15.26.32.43.47.	33.44.	
		(18W 19R) (18.31W 33R OR 44R)		
		(14.40W 44R)		
46	47.	38.48.		
47		5.6.33.36.44.45.		46
48		1.5.6.7.26.32.43.46.(4.15W 47N)	44.47.	
		(18W 19R. 47N) (18.31W 33R OR 44R)		
		(40W 44R)		
49	DETONATOR			
50	to 54: X			
55		18.23.56.	14.19.21.	59
56		14.18.19.21.31.40.43.55.57.58.	30.32.33.41.44.	
		(36.37 W 30R)		
57		14.18.19.21.31.40.43.56.	30.32.33.41.44.	59
		(36.37 W 30R)		
58	(57N MSL)	1.14.18.19.21.31.33.40.41.44.56.		59
59	55.57.58.			
	V.T. 5 BAR 4" CTRS	(INSTALLED 1953)		
	SPARE LEVER : 2			
	SHORT LEVER : 14			
	LOCKS (N) : 6.7.24.55.57.			
	(R) WITH RD : 22			
	(R) : 14			
	CONTACTS (2N) : 4.58			
	(2R) : 59			
X	ORIGINAL DRAWN: 14.2.1952	HIRWAUN		
W	ISSUED: 18.11.1953			
	REG No.	LOCKING TABLE		S /3/3