

FUNCTION	RELEASED OR CONTROLLED BY								REMARKS	
	SIGNAL	LEVER	LEVER LOCKED	DETECTION		TRACK CIRCUITS		BLOCK		
				NORMAL	REVERSE	CLEAR	OCC'D	L.C.		T.O.L.
9 (N) L								DOWN MN		ONE PULL
11 (N) L	12 ON		12N. 26R. 32R			11T. 26T. 32T. A32T				
12 (N) L								DOWN BCR		ONE PULL AFTER 11T OCCUPIED
26 (R) L						26T. (A32T w 69N)				ELN
32 (R) L						26T. 32T. A32T				ELN
46 (N) L	102 ON		102N		43A. 44.					
62 (R) L						62T				ELN
70 (R) L						70T. A32T				ELN
100 (N) L				58A	60					
101 (N) L			100	58A	60. 69A. 70					
102 (N) L								UP MAIN		ONE PULL AFTER 106T OCCUPIED
103 (N) L	102 ON		102. 62.		43A. 44. 58A. 60.	106T				
106 (N) L	102 ON		102. 103. 46. 70.	69A	70.	106T				
DOWN MAIN DISTANT (1A)	4 ON. 2.3. OFF	1R								
DOWN MAIN DISTANT (1B)	3 ON. 2.4. 11. 12 OFF	1R								
UP MAIN L.C.	107 SLOT ON		101. 106.							
DOWN MAIN L.C.	1A. 1. B. 2 ON	2N				2AT				
UP BRANCH L.C.		88. 105N								

DATED  
ISSUED 8.11.1967  
CORRECT TO V

ABER JCN

S1419 /5