

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
1	X			
2	23 (3.4 N MSL)	4.55.58.59		
3	23.68 (69W71R)	7.24.55.58.59. (83W70N71R)		
	(80W70N71R) (82W70R)	(97W70R)		
	(5.6.8 N ESL)			
4	22.23.24	2		
5	68	24.57.58.59.71	55	
6	68.69.71.80	7.57.58.83	55	
7	68.69.71.80	3.6.57.58.83	55	
8	68.69.70.82	57.58.97	55	
9-12	X			
13	DET.			
14	(15OR20)			
15	19	30.32.33.37.40	28	(14)
16		19.31.32.33.37	28	
17	(34W35R)	28.30.31.32. (40W19R)	19	
18	28.36	30.31.33 (40W19R)	19.29	
19		16.20.31.43.44.55. (21.27W24N)		15.30
20	26	19.24.40.41.42.43.44.55		(14)
21	26	27.43.44.55. (19.40W24N) (58W24R)		
22	26.27.36	41.42. (40W24N). (58W24R)	29	4
23	(26W24R)		24	2.3.4.53
24		3.5.20.41.42.43.44.55.59.71		4
25	X			
26			24.27	20.21.22.43.44 (23)(29)
27		21.28.35.43.44.55 (19W24N)		22.41.42

X	ORIGINAL DRAWN:	BARRY STATION	S1544 /3/1
	ISSUED:		
W	REG No.	LOCKING TABLE	

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
28		17.27.32.35		18.33
29	(26W27R)		27	33.41.42
30	19	15.17.18	28 (29W28R)	
31		16.17.18.19	28 (29W28R)	
32		15.16.17.28.34	19.35 (36W35R)	
33	28.29	15.16.18	19.36	
34	35	32.37	36	(17)
35		27.28		34.37
36			35	18.22.37
37	35.36	15.16.34		
38	DET			
39	x			
40		15.20.41.44.53.60.63. (17.18W19R)	19.55. (24W19N) (26W19.24N)	
		(21.22W24N)	(27W24N) (29W24N27R)	
41	27.29	20.22.24.40.42	36	
42	27.29 (40N ESL)	20.22.24.41	36	
43	26 (40N ESL)	19.20.21.24.27.44.55		
44	26	19.20.21.24.27.40.43.55		
45-48	x			
49-52	PERMANENT SPACES			
53	23.55.68. (69W71R)	40.57.59. (83W70N71R)		
	(80W70N71R)	(92W70R82N) (97W70.82R91N)		
54	68.69.70.82.91	57.58	55	
55		2.3.19.20.21.24.27.43.44.58		53.57
56			55	57.58.59
57	55.56	5.6.7.8.53.54	70.71. (82.83W71R) (84.91.92W70R) (97W70.82R)	60.61.63.64.67
X	ORIGINAL DRAWN: ISSUED:	<u>BARRY STATION</u> LOCKING TABLE		
W	REG No.			

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
58	56	2.3.5.6.7.8.54.55.(21.22W24R)	24.70.71.(26.27W24R)(82.83W71R)	
			(97W70.82R)(84.91.92W70R)(29W24.27R)	
59	56	2.3.5.24.53.71		
60	57.71.72	40.61.80.83		
61	57.71.72 (40NESL)	60.80.83		
62	x			
63	57.70.84	40.64.92		
64	57.70.84 (40NESL)	63.92		
65-66	x			
67	57.70.72.82.91			
68			71	3.5.6.7.8.53.54
69			70	(3).6.7.8.(53).54
70	71.83			8.54.63.64.67
71		5.24.59.79		6.7.60.61.70
72			70.71	60.61.67.78.81.85.(84)
73		88.90	89	
74	79.80	83		
75	79.82	97		
76	79.82.91	78		
77	x			
78	72.79.82.91	76		
79		71		74.75.76.78.81.85
80		60.61.81		6.7.74.(3).(53)
81	72.79	80.83		
82	83.92			8.54.67.75.76.78.(3)
83		6.7.60.61.74.81.89.(3.53W70W71R)		70.82.85

X	ORIGINAL DRAWN:	BARRY STATION	LOCKING TABLE
	ISSUED:		
W	REG No.	S1544 /3/3	

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
84	(72W83R)		83	63.64.85.90
85	79.83.84	92		
86	89.92	97		
87	89.91	88		
88	89.91	73.87		
89		83		86.87.88.90
90	84.89	73.92		
91	92.97			54.67.76.78.87.88
92		63.64.85.90.94.95.98.(53W70R82N)		82.86.91
93	x			
94		92.97		
95	97	92.98		
96	x			
97		8.75.86.94.99.(3W70R) (53W70.82R91N)		91.95.98
98	97	92.95		
99		97		
100-101	x			

X ORIGINAL DRAWN:
ISSUED: 16-4-57
W REG No.

BARRY STATION
LOCKING TABLE

V.T. 5BAR 4"
S1544 /3/4