

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
1	41. (40w39R)	19.38. (42.51w39R)		
2		26.29.33.34.37	38	(9 NOTCH 2 TO 3)
3	38.41. (40w39R)	30.35.37. (42.51w39R)	29.33.34. (26w34N). (32w33R)	(9 NOTCH 2 TO 3)
4	41	24.36.39. (30.35w38R)	19.37.38	(9 NOTCH 2 TO 3)
5	40.41	24.36.42.51. (30.35w38R)	19.37.38	
6		52	40.42.51. (41w40R)	
7	X			
8	X			
9	(2.3.4.47.49 NOTCH 2 TO 3)			
10	16. (19w17R)	23	17	
11	(19w17R)	15.16.23	17	
12	15. (19w17R)	20	17	
13	14.17		15.16	
14	19.41. (40w39R)	20.23.24. (42.51w39R). (56w17N)	17.18	13
15		11.16.23.30.36		12.20
16		11.15		10
17		57. (43w19N)		13.20.23
18			17	24.54.57.58.60
19		1.38.54.57.58.60		(10)(11)(12)14.24
20	15.17	12.14	18.19	(24)(54)
21	INTERLOCKING LEVER			(23)
22	INTERLOCKING LEVER			(23)
23	17. (21w16N). (22w16R)	10.11.14.15	16.18.19	(24)(54)
24	18.19. (20or 23w17R)	4.5.14	39.40.41. (42.51w40R)	
25	26	27		
26		2.29.37.47. (33w34N)		25.27

X ORIGINAL DRAWN: 6-10-41 JR1  
ISSUED: 12-1-53  
W REG No. L1167

HEREFORD BARTON CURVE  
LOCKING TABLE

S 2262 / 3/1

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
27	26	25		
28	(29 <sub>R</sub> 37)(41 <sub>W</sub> 37 <sub>R</sub> )(40 <sub>W</sub> 37.39 <sub>R</sub> )	30.36 (42.51 <sub>W</sub> 37.39 <sub>R</sub> )	38	
29		2.26.33.34.37		(28).30
30	29	3.15.28. (4.5 <sub>W</sub> 38 <sub>R</sub> )	38.(39.40.41 <sub>W</sub> 38 <sub>R</sub> )(42.51 <sub>W</sub> 38.40 <sub>R</sub> )	
31	33	35. (32 <sub>W</sub> 34 <sub>N</sub> )	34.38	
32		47.(31 <sub>W</sub> 34 <sub>N</sub> )(35 <sub>W</sub> 34 <sub>N</sub> )		34.48
33		2.29.37.47.48.49.55. (26 <sub>W</sub> 34 <sub>N</sub> )		31.35
34	32	2.29.37.48.49.55		
35	33	3.31.(4.5 <sub>W</sub> 38 <sub>R</sub> ).(32 <sub>W</sub> 34 <sub>N</sub> )	34.38.(39.40.41 <sub>W</sub> 38 <sub>R</sub> )(42.51 <sub>W</sub> 38.40 <sub>R</sub> )	
36	37	4.5.15.28	39.40.41. (42.51 <sub>W</sub> 40 <sub>R</sub> )	
37	38	2.3.26.29.33.34		(28).36
38	43	1.19.57		3.37
39		4		40.46
40	39			(1)(3).5(14)(28)
41			39	1.3.4.5.14(28)
42		5.51. (1.3.14 <sub>W</sub> 39 <sub>R</sub> ).(28 <sub>W</sub> 37.39 <sub>R</sub> )		
43		57.60. (17 <sub>W</sub> 19 <sub>N</sub> )		38.44
44	43			49.55
45			43	49.(52).55.58.60
46	39	49.60		55.58
47		26.32.33. (50 <sub>W</sub> 44.46 <sub>R</sub> )	44. (45.46 <sub>W</sub> 44 <sub>R</sub> )	(9 NOTCH 2 TO 3)
48	32	33.34. (50 <sub>W</sub> 44.46 <sub>R</sub> )	44. (45.46 <sub>W</sub> 44 <sub>R</sub> )	(9 NOTCH 2 TO 3)
49	44.45	33.34.46	32	
50	51	52.55.58. (47.48 <sub>W</sub> 44.46 <sub>R</sub> )(54.57 <sub>W</sub> 46 <sub>R</sub> )	46. (17.18.19 <sub>W</sub> 43 <sub>N</sub> 46 <sub>R</sub> )	
			(32.33.34 <sub>W</sub> 44.46 <sub>R</sub> )	
			(43.44.45 <sub>W</sub> 46 <sub>R</sub> )	

X ORIGINAL DRAWN:  
ISSUED:  
W REG No. L1167

HEREFORD BARTON CURVE  
LOCKING TABLE

S 2262 /3/2

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
51		5.42.53.59. (13.14W39R) (28W37.39R)		50.52
52	51. (45W46R)	6.50	46	
53		51.59		
54	18. (20or23)	19. (50W46R)	45.46	
55	44.45.46	33.34.50	32.51.53	
56		(14W17N)	17.18.19	
57	18	17.19.38.43. (50W46R)	45.46	
58	18.45.46	19.43.50	51.53	
59		51.53	46	
60	18.45	19.43.46		
	SHORT LEVERS:	9.21.22.42.53		
	LOCKS 'N' :	4.5.6.56.57		
	LOCKS 'N' & 'R' WITH SPL CONTACTS :	21.22		
	LOCKS 'N' & 'R' WITH RD CONTACTS :	39		
	LOCKS 'R' WITH RD CONTACTS:	42.43.53		

X ORIGINAL DRAWN: 6-10-41 JRI  
ISSUED: 12-1-53  
W REG No. L1167

HEREFORD BARTON CURVE  
LOCKING TABLE

V.T. SBAR 4"  
S 2262 /3/3