

GREAT WESTERN RAILWAY.

(For the use of the Company's servants only.)

SALISBURY—NEW SIGNAL AND GROUND FRAME.

On Friday, 31st July, 1942, between the hours of 8.30 a.m. and 4.0 p.m. or until the work is completed, the Signal Engineer will be engaged in bringing into use the following :—

NEW SIGNAL.

Form	Description	Position	Distance from Box.
	Up Main Advanced Starting.	Up side of Up Main.	898 yards.

* Signals will be renamed as shewn below :—

Existing	To become
Up Main Calling-on	From G.W. to Up Main Calling-on.
Backing from Down Main to Engine Shed or Cattle Pen Siding	Backing from Down G.W. to Engine Shed or Cattle Pens.
Up Main Outer Advanced Starting	Up Main Starting.
Up Main Advanced Starting	From G.W. to Up Main Starting.
Down Platform to Up Main Starting	From Down G.W. Platform Starting.
Up Main Starting	From Up G.W. Platform Starting.

A new trailing connection in the Up Main leading from the Exchange Siding will be brought into use together with a one-lever Ground Frame, to be known as "**Exchange Siding Ground Frame**" situated on the Up side of Exchange Siding, 815 yards the Wilton side of Salisbury G.W. Signal Box.

Electrical Interlocking and telephonic communication will be provided between the Ground Frame and the Salisbury G.W.R. Signal Box.

SIGNALLING RECORD SOCIETY

www.s-r-s.org.uk

DIGITAL ARCHIVE

This PDF Copy has been provided free of charge by David Allen in order to assist your research into UK signalling.

This file is one of a number scanned by David Allen using material from his own collection and from the collections of Phil Deaves, Robert Dey, David Ingham, Simon Lowe, John McCrickard, John Midcalf, Roger Newman, Richard Pulleyn and Chris Wolstenholmes. Thank you one and all. Many of the original documents are now in the SRS Archive or at the National Railway Museum.

You may also like to provide copies of Signalling Notices and Weekly (and periodical) Operating Notices as scans or as originals. The SRS is always willing to accept donations of any signalling or signalling related material for inclusion in the Society's Archive. Please contact the [Archivist](#) in the first instance.

For a list of PDFs currently available visit the list of [Weekly](#) Notices or [Signalling](#) Notices page.

If you have benefited from this PDF copy, why not [join](#) the Signalling Record Society and receive support for your researches and access to the Society's Archives

Members receive "The Signalling Record" six times annually plus a newsletter and have the opportunity to purchase SRS [books](#) and other [publications](#) at a discount. They also have access to back issues of The Newsletter and The Signalling Record which are only available to members. These contain a wealth of information accumulated since 1970, much of which is not readily available anywhere else.

In addition, Members have the opportunity to join signalling related visits to locations on the UK national and London Underground systems; and to other UK Railways.

To join the Signalling Record Society visit

www.s-r-s.org.uk/membform.html

Occupation of the Locking Frame will be required at the same time for the purpose of altering and testing locking.

The following Track Circuit will be brought into use :—

Signal Box	Track Circuit in rear of Signal named below	Length of Track	Position of Diamond Sign
Salisbury	Up Main Advanced Starting.	239 yards.	On Up Main Advanced Starting Signal.

District Inspector Old, Westbury, to make arrangements for safe working in accordance with Rule 77 and provide the necessary handsignalmen.

ACKNOWLEDGE RECEIPT TO HEAD OF DEPARTMENT.

TEMPLE MEADS STATION,
BRISTOL, July, 1942.

R. G. POLE,
Superintendent of the Bristol Division.

Received Notice S.1939, re Signal Alterations, Salisbury.

.....Department.

.....Station

.....Signature.


Mr. R. G. POLE,
Divisional Superintendent's Office,
Bristol.

SALISBURY.

SIGNAL BOX



FROM SALISBURY



EXCHANGE SIDING GROUND
FRAME. I. LEVER WORKING
POINTS * ELECTRICALLY RELEASED FROM
SIGNAL BOX. TELEPHONE TO S. B.

