PRIVATE and not for Publication

NOTICE No. W.W.350

# BRITISH RAILWAYS

(WESTERN REGION)

(For the use of employees only)

# SINGLING OF THE LINE BETWEEN ABERCYNON AND BLACK LION

Between the hours of 08.00 Saturday 23rd January and 06.00 Monday 25th January 1971 or until completion of work, the Chief Signal and Telecommunications Engineer and Divisional Civil Engineer will carry out the following work.

The existing Double line between Abercynon and Black Lion will become Single line. The Down line being used as the single line. Signalling and Permanent Way alterations will be carried out as shown on the attached sketch.

New signals will be brought into use as shown, descriptions as follows:-

	Description	Position	Distance from Box
A.	Down Main Distant	Down Side of Down Main Single Line	2,288 yards
	The height of	the signal will be 14 ft.	
В.	Down Main Home	Down Side of Down Main Single Line	908 yards
	The height of	the signal will be 14 ft.	
C.	Down Main Inner Home	Down Side of Down Main Single Line	465 yards
	The height of	the signal will be 26 ft.	
D.	Down Branch Distant The height of	Down Side of Down Branch the signal will be 14 ft.	1,602 yards
E.		Down Side of Down Branch the signal will be 14 ft.	535 yards
_			
F.		Up Side of Up Branch the signal will be 14 ft.	520 yards
G.	Existing Down Main Starting a Down Main Starting Bracket S New Down Main Lower Arm Stormstown, and Elevated Dis	Signal with Distant for	
H.	Down Main Advanced Starting with Lower Arm Inner Distant For Stormstown.	Down Side of Down Main Line	675 yards
	1 10 101010001 1000	the signal will be 27 ft. 9 in.	
	(This signal br	ought into use on 14th January, 197	71).
J.	Up Main Inner Home and Up Main Inner Home To up Branch Bracket.	Up Side of Up Main line	269 yards
	the second s	the signal will be 22 ft. 6 ins.	

New ground signals will be brought into use as shown on the attached sketch.

All existing signalling other than that shown on the attached sketch will be recovered.

## SIGNALLING RECORD SOCIETY

www.s-r-s.org.uk

### DIGITAL ARCHIVE

This PDF Copy has been provided free of charge by David Allen in order to assist your research into UK signalling.

This file is one of a number scanned by David Allen using material from his own collection and from the collections of Phil Deaves, Robert Dey, David Ingham, Simon Lowe, John McCrickard, John Midcalf, Richard Maund, Richard Pulleyn, Roger Newman and Chris Wolstenholmes. Thank you one and all. Many of the original documents are now in the SRS Archive or at the National Railway Museum.

You may also like to provide copies of Signalling Notices and Weekly (and periodical) Operating Notices or other notices as scans or as originals. The SRS is always willing to accept donations of any signalling or signalling related material for inclusion in the Society's Archive. Please contact the <u>Archivist</u> in the first instance.

For a list of PDFs currently available visit the <u>Archives</u> pages of the SRS Web Site.

If you have benefited from this PDF copy, why not join the Signalling Record Society and receive support for your researches and access to the Society's Archives

Members receive "The Signalling Record" six times annually plus a newsletter and have the opportunity to purchase SRS <u>books</u> and other <u>publications</u> at a discount. They also have access to back issues of The Newsletter and The Signalling Record which are only available to members. These contain a wealth of information accumulated since 1970, much of which is not readily available anywhere else.

In addition, Members have the opportunity to join signalling related visits to locations on the UK national and London Underground systems; and to other UK Railways.

To join the Signalling Record Society visit

www.s-r-s.org.uk/membform.html

The new connection from Down Main to Through Siding and the Main Single Line safety point will be motor operated with Hand Generator Standby. The electric point machines will be W.B. & S. Co's Style 'C', emergency operating instructions for which are issued separately.

New track circuits will be provided as necessary.

Block sections will be altered as follows:-

Existing Double Line Section Abercynon to Black Lion to become a single Line Section worked by Electric Token.

The Up Main Starting Signal to Black Lion will become released by Token withdrawn. This release will be effective for 'one pull' only. The New Up Branch Starting Signal to Abercymboi will also become released by token withdrawn with a similar 'one pull' feature. In addition a new auxilliary token instrument will be provided on the Abercynon—Abercymboi section at a hut adjacent to the new Up Branch Starting Signal.

The New Down Main Advanced Starting Signal will become released by Line clear 'for one pull after berth track circuit occupied'.

Telephones to Abercynon Signal Box will be provided from the new Auxilliary Token Hut, and the new motor operated points.

The telephone situated at the present Down Branch Home Signal will remain in situ, as a line side telephone.

Occupation of the Locking Frame will be required for the purpose of re-locking and testing the frame.

### BLACK LION SIGNAL BOX

At Black Lion the exisiting Up Main Home Signal will now apply to the new single line, the existing main trailing crossover will be fitted with a facing point lock in the Up direction. The existing Up Main distant will also apply to the single line.

Occupation of the locking frame will be required for altering and testing the locking.

District Signalling Inspector, Pontypridd, to make all arrangements for safe working including the appointment of the necessary Handsignalmen in accordance with Rule 77.

PLEASE ACKNOWLEDGE RECEIPT ON FORM BELOW

4th January, 1971 Cardiff (Extn. 2473)

### E. R. WILLIAMS,

Divisional Manager.

### Singling of the line between Abercynon and Black Lion

I have received copy/copies of Notice W.W.350 dated 4th January, 1971 in connection with the above.

Date		Date
------	--	------

Station

Dept. Signature

E. R. WILLIAMS, Esq., C.P. 16, Room 351, Marland House, Cardiff.

